

PRODUCT DATA SHEET

Issue on 14 April 2017
Texas Petrochemical Asia Pacific Pte Ltd

Singapore 629170 Tel: 65-6262 6538 Fax: 65-6262 6537 Website: <u>www.texaslub.com</u>

TEXAS TEXMARINE CLS 400

Superior Quality Cylinder Lubricant

DESCRIPTION

TEXAS TEXMARINE CLS 400 is alkaline marine diesel engine cylinder lubrication suitable for improving piston running conditions in low speed diesel engines and burning low Sulphur fuels.

PERFORMANCE STANDARDS

API CF

MAIN APPLICATION

- Cylinder Lubrication of low speed marine diesel engines burning residual fuels with Sulphur content less than 1.5%
- Industrial Engines (Power Station)

BENEFITS

- High level of dispersion and detergency
- Excellent resistance to oxidation at high temperatures
- High load carrying capacity
- Excellent anti-wear, anti-rust and anti- foaming properties

TYPICAL PROPERTIES

TEXMARINE 400	SAE 50
Density, kg/Litre @ 15°C	0.916
Kinematic Viscosity, mm ² /s @ 40°C	233.9
Kinematic Viscosity, mm ² /s @ 100°C	20.0
Viscosity Index	99
Pour Point, °C	-6
Flash Point COC, °C	240
TBN	40